

Accede

Type 260-P/260-S

	Type 260 S	Type 260 P
Foil width Max. (mm)	260	
Rows Sealing Roll (Rows)	4-8	
Foil Diameter Max. (mm)	Ø 340	
Foil Sensor	Yes	No
Capacity (tablet/hour)	30.000 for Sealing Roll 6 Rows	
Motor Drive	1/2 HP, AC Variable Speed Motor ex. Italia	
Gear Box	1/2 HP, Ratio 1 : 10 ex. Italia	
Vibrator Feeder	Ex. Germany	
Linear Feeder	Ex. Germany	
Product Sensor	Yes	No
Electric Consumption	3.1 Kw, 10 Ampere, 3 Phase, 220/380 Volt, 50 Hz	
Controller	PLC	Manual
Monitor	Touch Screen	Manual
Air Pressure	5 Bar FESTO ex. Germany	
Dimension (mm)	1,350 x 1,500 x 1,950	
Material Change Parts:		
- Frame Material	Mild Steel with Paint	
- Cover	St-Steel 304	
- Feeding Guide	Aluminium Anodize	
- Feeding Plate	Aluminium Anodize	
- Sealing Rooll	St-Steel 316	
- Change Gear	AISI - 1045	
Optional	Coding Ink System	

